

The StaticHTMLExporter Task

Overview document

The StaticHTMLExporter is a task that downloads HTML pages from a server and saves them as HTML files. It needs the following parameters:

- **server-uri**: the server uri, e. g. `http://authoring.yourdomain.com`
- **server-port**: the server port, e. g. 8080
- **publication-id**: the publication id
- **export-path-prefix**: the path to save the files to
- **uris**: a comma-separated list of uris to download (without server + port)
- **substitute-regexp**: a regular expression to substitute a part of the path

Usually, the path information is read from the `[publication-directory]/config/publishing/publisher.xconf` file:

```
<publication>
  ...
  <export>
    <destination href="work/export/pending"/>
    <substitution regexp="s/\\lenya\\unipublic//g"/>
  </export>
</publication>
```

You can override the paths in the task configuration file `tasks.xconf`, e. g. to use several publishers to publish into different directories:

```
<tasks>

  <task id="export-pending" class="org.apache.lenya.cms.publishing.StaticHTMLExporter">
    <parameter name="export-path" value="work/export/pending"/>
    <parameter name="substitute-regexp" value="s/\\lenya\\your-publication//g"/>
  </task>

  <task id="export-backup" class="org.apache.lenya.cms.publishing.StaticHTMLExporter">
    <parameter name="export-path" value="work/backup"/>
    <parameter name="substitute-regexp" value="s/\\lenya\\your-publication//g"/>
  </task>

</tasks>
```