

Testing Security 2

Example testing-security-2 can be browsed at <https://github.com/apache/tomee/tree/master/examples/testing-security-2>

Help us document this example! Click the blue pencil icon in the upper right to edit this page.

Movie

```
package org.superbiz.injection.secure;

import javax.persistence.Entity;

@Entity
public class Movie {

    private String director;
    private String title;
    private int year;

    public Movie() {
    }

    public Movie(String director, String title, int year) {
        this.director = director;
        this.title = title;
        this.year = year;
    }

    public String getDirector() {
        return director;
    }

    public void setDirector(String director) {
        this.director = director;
    }

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public int getYear() {
        return year;
    }

    public void setYear(int year) {
        this.year = year;
    }
}
```

Movies

```
package org.superbiz.injection.secure;

//START SNIPPET: code

import javax.annotation.security.PermitAll;
import javax.annotation.security.RolesAllowed;
import javax.ejb.Stateful;
import javax.ejb.TransactionAttribute;
import javax.ejb.TransactionAttributeType;
import javax.persistence.EntityManager;
import javax.persistence.PersistenceContext;
import javax.persistence.PersistenceContextType;
import javax.persistence.Query;
import java.util.List;

@Stateful
public class Movies {

    @PersistenceContext(unitName = "movie-unit", type = PersistenceContextType
.EXTENDED)
    private EntityManager entityManager;

    @RolesAllowed({"Employee", "Manager"})
    public void addMovie(Movie movie) throws Exception {
        entityManager.persist(movie);
    }

    @RolesAllowed({"Manager"})
    public void deleteMovie(Movie movie) throws Exception {
        entityManager.remove(movie);
    }

    @PermitAll
    @TransactionAttribute(TransactionAttributeType.SUPPORTS)
    public List<Movie> getMovies() throws Exception {
        Query query = entityManager.createQuery("SELECT m from Movie as m");
        return query.getResultList();
    }
}
```

persistence.xml

```

<persistence xmlns="http://java.sun.com/xml/ns/persistence" version="1.0">

  <persistence-unit name="movie-unit">
    <jta-data-source>movieDatabase</jta-data-source>
    <non-jta-data-source>movieDatabaseUnmanaged</non-jta-data-source>
    <class>org.superbiz.injection.secure.Movie</class>

    <properties>
      <property name="openjpa.jdbc.SynchronizeMappings" value=
"buildSchema(ForeignKeys=true)"/>
    </properties>
  </persistence-unit>
</persistence>

```

MovieTest

```

package org.superbiz.injection.secure;

import junit.framework.TestCase;

import javax.ejb.EJB;
import javax.ejb.EJBAccessException;
import javax.ejb.embeddable.EJBContainer;
import javax.naming.Context;
import javax.naming.InitialContext;
import java.util.List;
import java.util.Properties;

//START SNIPPET: code
public class MovieTest extends TestCase {

    @EJB
    private Movies movies;

    protected void setUp() throws Exception {

        // Uncomment this line to set the login/logout functionality on Debug
        //System.setProperty("log4j.category.OpenEJB.security", "debug");

        Properties p = new Properties();
        p.put("movieDatabase", "new://Resource?type=DataSource");
        p.put("movieDatabase.JdbcDriver", "org.hsqldb.jdbcDriver");
        p.put("movieDatabase.JdbcUrl", "jdbc:hsqldb:mem:moviedb");

        EJBContainer.createEJBContainer(p).getContext().bind("inject", this);
    }

    public void testAsManager() throws Exception {

```

```

Properties p = new Properties();
p.put(Context.INITIAL_CONTEXT_FACTORY,
"org.apache.openejb.core.LocalInitialContextFactory");
p.put(Context.SECURITY_PRINCIPAL, "jane");
p.put(Context.SECURITY_CREDENTIALS, "waterfall");

InitialContext context = new InitialContext(p);

try {
    movies.addMovie(new Movie("Quentin Tarantino", "Reservoir Dogs", 1992));
    movies.addMovie(new Movie("Joel Coen", "Fargo", 1996));
    movies.addMovie(new Movie("Joel Coen", "The Big Lebowski", 1998));

    List<Movie> list = movies.getMovies();
    assertEquals("List.size()", 3, list.size());

    for (Movie movie : list) {
        movies.deleteMovie(movie);
    }

    assertEquals("Movies.getMovies()", 0, movies.getMovies().size());
} finally {
    context.close();
}
}

public void testAsEmployee() throws Exception {
    Properties p = new Properties();
    p.put(Context.INITIAL_CONTEXT_FACTORY,
"org.apache.openejb.core.LocalInitialContextFactory");
    p.put(Context.SECURITY_PRINCIPAL, "joe");
    p.put(Context.SECURITY_CREDENTIALS, "cool");

    InitialContext context = new InitialContext(p);

    try {
        movies.addMovie(new Movie("Quentin Tarantino", "Reservoir Dogs", 1992));
        movies.addMovie(new Movie("Joel Coen", "Fargo", 1996));
        movies.addMovie(new Movie("Joel Coen", "The Big Lebowski", 1998));

        List<Movie> list = movies.getMovies();
        assertEquals("List.size()", 3, list.size());

        for (Movie movie : list) {
            try {
                movies.deleteMovie(movie);
                fail("Employees should not be allowed to delete");
            } catch (EJBAccessException e) {
                // Good, Employees cannot delete things
            }
        }
    }
}

```

```

        // The list should still be three movies long
        assertEquals("Movies.getMovies()", 3, movies.getMovies().size());
    } finally {
        context.close();
    }
}

public void testUnauthenticated() throws Exception {
    try {
        movies.addMovie(new Movie("Quentin Tarantino", "Reservoir Dogs", 1992));
        fail("Unauthenticated users should not be able to add movies");
    } catch (EJBAccessException e) {
        // Good, guests cannot add things
    }

    try {
        movies.deleteMovie(null);
        fail("Unauthenticated users should not be allowed to delete");
    } catch (EJBAccessException e) {
        // Good, Unauthenticated users cannot delete things
    }

    try {
        // Read access should be allowed

        List<Movie> list = movies.getMovies();
    } catch (EJBAccessException e) {
        fail("Read access should be allowed");
    }
}
}
}

```

Running

T E S T S

```

Running org.superbiz.injection.secure.MovieTest
Apache OpenEJB 4.0.0-beta-1    build: 20111002-04:06
http://tomee.apache.org/
INFO - openejb.home = /Users/dblevins/examples/testing-security-2
INFO - openejb.base = /Users/dblevins/examples/testing-security-2
INFO - Using 'javax.ejb.embeddable.EJBContainer=true'
INFO - Configuring Service(id=Default Security Service, type=SecurityService,
provider-id=Default Security Service)
INFO - Configuring Service(id=Default Transaction Manager, type=TransactionManager,
provider-id=Default Transaction Manager)

```

```
INFO - Configuring Service(id=movieDatabase, type=Resource, provider-id=Default JDBC
Database)
INFO - Found EjbModule in classpath: /Users/dblevins/examples/testing-security-
2/target/classes
INFO - Beginning load: /Users/dblevins/examples/testing-security-2/target/classes
INFO - Configuring enterprise application: /Users/dblevins/examples/testing-security-2
INFO - Configuring Service(id=Default Stateful Container, type=Container, provider-
id=Default Stateful Container)
INFO - Auto-creating a container for bean Movies: Container(type=STATEFUL, id=Default
Stateful Container)
INFO - Configuring Service(id=Default Managed Container, type=Container, provider-
id=Default Managed Container)
INFO - Auto-creating a container for bean org.superbiz.injection.secure.MovieTest:
Container(type=MANAGED, id=Default Managed Container)
INFO - Configuring PersistenceUnit(name=movie-unit)
INFO - Auto-creating a Resource with id 'movieDatabaseNonJta' of type 'DataSource for
'movie-unit'.
INFO - Configuring Service(id=movieDatabaseNonJta, type=Resource, provider-
id=movieDatabase)
INFO - Adjusting PersistenceUnit movie-unit <non-jta-data-source> to Resource ID
'movieDatabaseNonJta' from 'movieDatabaseUnmanaged'
INFO - Enterprise application "/Users/dblevins/examples/testing-security-2" loaded.
INFO - Assembling app: /Users/dblevins/examples/testing-security-2
INFO - PersistenceUnit(name=movie-unit,
provider=org.apache.openjpa.persistence.PersistenceProviderImpl) - provider time 413ms
INFO - Jndi(name="java:global/testing-security-
2/Movies!org.superbiz.injection.secure.Movies")
INFO - Jndi(name="java:global/testing-security-2/Movies")
INFO -
Jndi(name="java:global/EjbModule1634151355/org.superbiz.injection.secure.MovieTest!org
.superbiz.injection.secure.MovieTest")
INFO -
Jndi(name="java:global/EjbModule1634151355/org.superbiz.injection.secure.MovieTest")
INFO - Created Ejb(deployment-id=Movies, ejb-name=Movies, container=Default Stateful
Container)
INFO - Created Ejb(deployment-id=org.superbiz.injection.secure.MovieTest, ejb-
name=org.superbiz.injection.secure.MovieTest, container=Default Managed Container)
INFO - Started Ejb(deployment-id=Movies, ejb-name=Movies, container=Default Stateful
Container)
INFO - Started Ejb(deployment-id=org.superbiz.injection.secure.MovieTest, ejb-
name=org.superbiz.injection.secure.MovieTest, container=Default Managed Container)
INFO - Deployed Application(path=/Users/dblevins/examples/testing-security-2)
INFO - Logging in
INFO - Logging out
INFO - EJBContainer already initialized. Call ejbContainer.close() to allow
reinitialization
INFO - Logging in
INFO - Logging out
INFO - EJBContainer already initialized. Call ejbContainer.close() to allow
reinitialization
Tests run: 3, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 2.546 sec
```


Results :

Tests run: 3, Failures: 0, Errors: 0, Skipped: 0