

How to create a PDF document for each tab

This How-To describes the generation of a PDF document for each group of documents that is defined by a tab.

Table of contents

1 Intended Audience.....	2
2 Purpose.....	2
3 Prerequisites.....	2
4 Steps.....	2
4.1 Create your project's main sitemap.xmap.....	2
4.2 Create another sitemap: pdf-tab.xmap.....	2
4.3 Edit project sitemap.xmap to mount pdf-tab.xmap.....	2
4.4 Edit the file pdf-tab.xmap.....	2
4.5 Edit your site.xml.....	3
4.6 Explanation of the operation.....	4
5 Feedback and further development of this How-To.....	4

1 Intended Audience

Users who need to generate one printable document aggregated from a group of documents.

2 Purpose

By default Forrest generates a pdf file for each separate document of your project. As well you can create a pdf of the whole site. But sometimes it may be necessary to generate a pdf file out of selected tab, i.e. only for certain parts of the site.

3 Prerequisites

- Understand how to create project-specific sitemaps by following the [Using Forrest](#) document.

4 Steps

The procedure outlined below will define a project `sitemap.xmap` and create a new `pdf-tab.xmap`.

4.1 Create your project's main `sitemap.xmap`

If you do not have already a sitemap then create a new empty one in your `src/documentation` directory (or wherever `${project.sitemap-dir}` points to).

4.2 Create another sitemap: `pdf-tab.xmap`

Like before create an empty sitemap and name it `pdf-tab.xmap`.

4.3 Edit project `sitemap.xmap` to mount `pdf-tab.xmap`

Your sitemap should look something like this.

```
<map:sitemap xmlns:map="http://apache.org/cocoon/sitemap/1.0">
  <map:pipelines>
    <map:pipeline internal-only="false">
      <map:match pattern="*.xml">
        <!-- pdf-tab definitions -->
        <map:match pattern="pdf-tab.xml">
          <map:mount uri-prefix="" src="pdf-tab.xmap"
            check-reload="yes" />
        </map:match>
        <!-- end of pdf-tab definitions -->
      </map:match>
    </map:pipeline>
  </map:pipelines>
</map:sitemap>
```

4.4 Edit the file `pdf-tab.xmap`

The `<map:match pattern="*.xml">` element should look like the following:

```
<map:sitemap xmlns:map="http://apache.org/cocoon/sitemap/1.0">
  <map:pipelines>
    <map:pipeline internal-only="false">
```

```

<map:match pattern="*.xml">
<map:generate src="cocoon://abs-linkmap"/>
<map:transform type="xpath">
  <map:parameter name="include" value="//*[@wholesite='true']"/>
<map:parameter name="exclude" value="//*[@wholesite='false']"/>
</map:transform>
<map:transform src="resources/stylesheets/site2book.xsl" />
<map:transform src="resources/stylesheets/aggregates/book2cinclue.xsl">
  <map:parameter name="title"
value="{conf:project-name}: Still My Foo Site"/>
</map:transform>
<map:transform type="cinclue"/>
<map:transform src="resources/stylesheets/aggregates/doc2doc-uniqueids.xsl"/>
<map:transform src="resources/stylesheets/aggregates/docs2document.xsl"/>
<map:serialize type="xml"/>
</map:match>
</map:pipeline>
</map:pipelines>
</map:sitemap>

```

4.5 Edit your site.xml

Note:

Do not use directories with "." in it. Replace them by "_" e.g 1.2/ will not work in the aggregation. e.g. 1_2/ just works fine.

Add the following entry to your site.xml in the `<about>` element

```
...
<whole_foosite href="pdf-tab.html" label="sub site" />
```

Your site.xml should look like this ...

```
...
<about label="About">
  <index label="Index" href="index.html" description="Welcome to MyProj"/>
  <changes label="Changes" href="changes.html"
    description="History of Changes" />
  <todo label="Todo" href="todo.html" description="Todo List" />
  <whole_foosite href="pdf-tab.html" label="pdf-tab" />
</about>
...
```

This allows you to link to it via a `<link href="site:whole_foosite">` reference.

Add to every element that should be included in the pdf-tab.pdf the attribute `wholesite="true"`

```
<sample-wiki label="Wiki page" href="wiki-sample.html"
  description="wiki-sample" wholesite="true"/>
```

Note:

This attribute will be inherited by all children of the element. Do not use it in the parent element that contains the `<whole_foosite href="pdf-tab.html" label="pdf-tab" />` as the child (will cause a stack overflow if you do)!!!

4.6 Explanation of the operation

Line 4 of our example

<map:parameter name="include" value="//*[@wholesite='true']"/> looks at your site.xml and will match every element containing the wholesite="true" attribute. For example, to use the "samples" tab ...

```
...
<samples label="Samples" href="samples/" tab="samples" wholesite="true">
...
</samples>
...
```

It matches **all** of the elements that contain wholesite="true" (in our example <samples> and its "children") for the content of the pdf file to be generated.

```
<samples label="Samples" href="samples/" tab="samples" wholesite="true">
<sample2 label="Static content" href="sample2.html"
  description="More Samples" wholesite='false' />
<sample-wiki label="Wiki page" href="wiki-sample.html"
  description="wiki-sample" />
<sample-ihtml label="ihtml page" href="ihtml-sample.html"
  description="Test iHTML page" />
</samples>
```

This example shows that you can as well exclude site(s) from the aggregation by using the wholesite="false" attribute. This attribute will be as well inherited by all children of the element.

Line 8 defines the title of the pdf file by taking the content of the project-name variable in skinconf.xml and adding some funny text:

```
<map:parameter name="title" value="{conf:project-name}: Still My Foo Site"/>
```

5 Feedback and further development of this How-To

Please provide feedback about this document via the [mailing lists](#).

In the future, this ability will probably be incorporated into the main Forrest process.