

# Upgrading to Apache Forrest 0.8

## Table of contents

1 Introduction.....	2
2 New Features.....	2
3 Locationmaps.....	2
4 Prototype xml-based properties system.....	2
5 Forrest configuration simplification.....	2
6 Run a clean target after upgrade.....	3
7 New filename convention for stylesheets.....	3
8 Notes about documentation.....	3
9 Notes about Cocoon version.....	3
10 The "wholesite" aggregation is not functioning.....	3
11 Whitespace and indenting of xml files with xmlformat.....	3
12 General upgrade tips.....	3
13 Remove project sitemap if not necessary.....	4
14 To be continued.....	4

## 1 Introduction

This page describes some changes to Apache Forrest that affect people who are upgrading to the 0.8 version. If you have other issues, then please discuss on either the [dev](#) or [user](#) mailing lists. As more experience is gained, this document will be updated.

(If you are upgrading from a version prior to 0.7 then you will need to see the notes for the previous upgrade.)

## 2 New Features

The following list shows some of the key new features. For the full list of changes, see the main [change log](#) and also for each plugin.

- [Locationmaps](#).

Many new initial plugins are in the "whiteboard". See the entries in the [change log](#) and see each plugin's documentation and changes log. This includes the new Dispatcher. See [Status of Themes: Skins and Dispatcher](#).

## 3 Locationmaps

The [Locationmaps](#) define the mapping from requests to locations which enables content and resources to be located at various different sources.

Adding a default locationmap to your project is not required, but is advisable. Sooner or later you will use it. Having a default one also reduces the verbosity of the log files. Copy one from a fresh 'forrest seed' to `PROJECT_HOME/src/documentation/content/locationmap.xml`

### Warning:

If you do use locationmaps and an entry for a specific request is missing Forrest generates a confusing error message. Please ask on our mailing lists for help in debugging your problem (hint, turn on locationmap debugging in `[FORREST_HOME]/main/webapp/WEB-INF/logkit.xconf`, restart Forrest, request the broken pages and visit `[SITE_HOME]/build/webapp/logs/locationmap.xml`). This issue will be fixed in the next version of Forrest.

## 4 Prototype xml-based properties system

Prototype of new xml-based properties system. Projects and plugins can use a `forrest.properties.xml` file. At this stage, it supplements the existing `forrest.properties` file. See the `projectInfo` plugin for an example of its use. Search the dev mailing list for more information.

## 5 Forrest configuration simplification

**FOR-920** Merging the defaults and project modules to the new properties module. You can use it like `{properties:forrest.home}`

In all custom code (e.g. [project sitemap](#) or [plugins sitemaps](#)) you need to do the following:

- find: `{defaults:}` and replace with `{properties:forrest.}`
- find: `{forrest:}` and replace with `{forrest:forrest.}` or `{properties:forrest.}` (if you do not need the `ChainMetaModule`)
- find: `{project:}` and replace with `{properties:}`

The consequence of not making such corrections is an error message similar to the following:

```
Could not find component for role:
[org.apache.cocoon.components.modules.input.InputModule/project]
```

The most likely culprit is forgetting to edit your "project sitemap" explained [below](#). See the [glossary](#) if you are confused by terminology.

## 6 Run a clean target after upgrade

Do 'forrest clean-work' in each of your projects. This also removes the old Cocoon disk cache.

## 7 New filename convention for stylesheets

There is now a filenaming convention for stylesheets (e.g. document-to-html.xml). This assists with automating the location of such resources. See [Locationmap](#).

For the default use of Forrest, this makes no difference. However, if you have developed your own skin then you will need to do some filename changes, e.g. 'cd skins/my-skin/xslt/html; mv tab2menu.xml tab-to-menu.xml' (do each of book2menu.xml document2html.xml site2html.xml tab2menu.xml). It is advisable to follow this naming convention for your other resources, which will mean that you can utilise the locationmap.

## 8 Notes about documentation

After each release, the "Versioned Docs" are copied to form the new "dev" set. Ideally the docs are then upgraded in readiness for the new release. This has not been completed for the 0.8 release. In particular there are example snippets of sitemaps which have not yet been upgraded to reflect the changes to the sitemaps and the separation of some core stuff into plugins. See issues [FOR-546](#) and [FOR-922](#) and others.

## 9 Notes about Cocoon version

The last time that we upgraded our packaged version of Cocoon trunk was using their SVN r351990 on 2005-12-08. Since then a number of things have happened to cause us to fall out of synchronisation with Cocoon. There is various discussion about this in the Forrest and Cocoon dev mail archives.

If you use your own version of Cocoon, then you will know about the upgrade notes in the \$FORREST\_HOME/etc/cocoon\_upgrade directory. You might be able to advance a bit beyond the SVN revision, but not much. Please help to rectify this situation. See [FOR-1015](#).

## 10 The "wholesite" aggregation is not functioning

See notes in the [FAQ](#) about "wholesite".

## 11 Whitespace and indenting of xml files with xmlformat

All xml type files have been formatted using xmlformat. You can apply this to your own work if necessary by using the same configuration as the Forrest project. See notes at [FOR-644](#).

## 12 General upgrade tips

Synchronise your project's skinconf.xml and forrest.properties files.

Take advantage of the separation of concerns. In a new workspace, create a fresh 'forrest seed' site, then tweak its `forrest.properties` and `skinconf.xml` until it reflects your old site. When it is ready, replace your project's `skinconf.xml` and `forrest.properties` files. Any remaining issues would concern other aspects of your configuration, such as `site.xml` and your actual content.

### 13 Remove project sitemap if not necessary

---

It has come to our attention that some people have a [project sitemap](#) even though they are not using it. Such un-necessary sitemaps should be removed to avoid maintenance issues.

If you do use a project sitemap, then pay attention to the upgrade instructions "[Forrest configuration simplification](#)" above.

### 14 To be continued...

---

...as more issues are discovered/remembered :) Please send feedback to the [mailing list](#).