

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	5
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	6
3.9 .....	7
3.10 .....	7
3.11 .....	8
3.12 .....	8
3.13 .....	8
3.14 .....	9
3.15 .....	9
3.16 .....	10
3.17 .....	10
3.18 .....	10
3.19 .....	11
3.20 .....	11
3.21 .....	11
3.22 .....	12
3.23 .....	12
3.24 .....	12
3.25 .....	13
3.26 .....	13
3.27 .....	14
3.28 .....	14

---

3.29 .....	14
3.30 .....	15
3.31 .....	15
3.32 .....	15
3.33 .....	16
3.34 .....	16
3.35 .....	16
3.36 .....	17
3.37 .....	17
3.38 .....	17
3.39 .....	18
3.40 .....	18
3.41 .....	18
3.42 .....	19
3.43 .....	19
3.44 .....	19
3.45 .....	19
3.46 .....	20
3.47 .....	20
3.48 .....	20
3.49 .....	21
3.50 .....	21
3.51 .....	21

## 1. Top-level element(s)

---

- [document](#)
- [faqs](#)

## 2. List of elements

---

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [icon](#)
- [img](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)

- [table](#)
- [td](#)
- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person			
Content model		EMPTY	
Attributes			
		id	type: required
		class	type: required
		xml:lang	type: required
		name	type: required
		email	type: required
Used inside		<a href="#">authors</a>	

#### 3.2.

strong			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes			
		id	type: required
		class	type: required
		xml:lang	type: required
Used inside		<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.3.

em		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.4.

code		
Content model	( #PCDATA )	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.5.

sup		
Content model	( #PCDATA )	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>	

	<a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

### 3.6.

sub			
Content model	( #PCDATA )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.7.

a			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	title		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.8.

br			
Content model	EMPTY		
Attributes	id		type:

	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.9.

img			
Content model	EMPTY		
Attributes	src		type: require
	alt		type: require
	height		type:
	width		type:
	usemap		type:
	ismap		possib
	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.10.

map			
Content model	( <a href="#">area</a> + )		
Attributes	name		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.11.

area			
Content model		EMPTY	
Attributes			
		shape	default: possible: default:
		coords	type:
		href	type: required:
		title	type:
		nohref	possible:
		alt	type: required:
Used inside		<a href="#">map</a>	

### 3.12.

icon			
Content model		EMPTY	
Attributes			
		src	type: required:
		alt	type: required:
		height	type:
		width	type:
		id	type:
		class	type:
		xml:lang	type:
Used inside		<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.13.

acronym			
Content model	( #PCDATA ) *		
Attributes	title		type: required
	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.14.

p			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	xml:space		possible presence:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.15.

source			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	xml:space		default fixed value possible presence:

Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

### 3.16.

note			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.17.

warning			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.18.

fixme			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	author		type: require
	id		type:
	class		type:

	xml:lang		type:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.19.

table			
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.20.

caption			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">table</a>		

### 3.21.

tr			
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">table</a>		

--

### 3.22.

th		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
	colspan	type: default
	rowspan	type: default
Used inside	<a href="#">tr</a>	

### 3.23.

td		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
	colspan	type: default
	rowspan	type: default
Used inside	<a href="#">tr</a>	

### 3.24.

li
----

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">ul</a>   <a href="#">ol</a>		

### 3.25.

ul			
Content model	( <a href="#">li</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possibl comp
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.26.

ol			
Content model	( <a href="#">li</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possibl comp
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.27.

dl		
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.28.

dt		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">dl</a>	

### 3.29.

dd		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">dl</a>	

### 3.30.

figure			
Content model		EMPTY	
Attributes			
	src		type: required
	alt		type: required
	height		type:
	width		type:
	usemap		type:
	ismap		possib
	align		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.31.

anchor			
Content model		EMPTY	
Attributes			
	id		type: required
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.32.

document	
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )

Attributes	id		type:
	class		type:
	xml:lang		type:

### 3.33.

header			
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">meta</a> * )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">document</a>		

### 3.34.

title			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">a</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">faqs</a>   <a href="#">faqsection</a>		

### 3.35.

subtitle			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

--

### 3.36.

version			
Content model		( #PCDATA )	
Attributes	id		type:
	class		type:
	xml:lang		type:
	major		type:
	minor		type:
	fix		type:
	tag		type:
Used inside		<a href="#">header</a>	

### 3.37.

type			
Content model		( #PCDATA )	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">header</a>	

### 3.38.

authors			
Content model		( <a href="#">person</a> + )	
Attributes	id		type:
	class		type:
	xml:lang		type:

Used inside	<a href="#">header</a>   <a href="#">faqs</a>

### 3.39.

notice			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

### 3.40.

abstract			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

### 3.41.

meta			
Content model	( #PCDATA )		
Attributes	name		type: required
	id		type:
	class		type:
	xml:lang		type:

Used inside	<a href="#">header</a>

### 3.42.

body			
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">document</a>		

### 3.43.

section			
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">body</a>   <a href="#">section</a>		

### 3.44.

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

### 3.45.

legal	
Content model	( <a href="#">#PCDATA</a>   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">footer</a>		

### 3.46.

faqs			
Content model	( <a href="#">title</a> ? , <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )		
Attributes	id		type:
	class		type:
	xml:lang		type:

### 3.47.

faqsection			
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>		

### 3.48.

faq			
Content model	( <a href="#">question</a> , <a href="#">answer</a> )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>		

### 3.49.

question		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">elaboration</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">faq</a>	

### 3.50.

elaboration		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	<a href="#">question</a>	

### 3.51.

answer		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	author	type:
Used inside	<a href="#">faq</a>	