

# Hadoop Quick Start

## Table of contents

1 Purpose.....	2
2 Pre-requisites.....	2
2.1 Supported Platforms.....	2
2.2 Required Software.....	2
2.3 Installing Software.....	2
3 Download.....	2
4 Prepare to Start the Hadoop Cluster.....	3
5 Standalone Operation.....	3
6 Pseudo-Distributed Operation.....	3
6.1 Configuration.....	3
6.2 Setup passphraseless ssh.....	4
6.3 Execution.....	4
7 Fully-Distributed Operation.....	5

## 1. Purpose

The purpose of this document is to help you get a single-node Hadoop installation up and running very quickly so that you can get a flavour of the Hadoop Distributed File System (see [HDFS Architecture](#)) and the Map/Reduce framework; that is, perform simple operations on HDFS and run example jobs.

## 2. Pre-requisites

### 2.1. Supported Platforms

- GNU/Linux is supported as a development and production platform. Hadoop has been demonstrated on GNU/Linux clusters with 2000 nodes.
- Win32 is supported as a *development platform*. Distributed operation has not been well tested on Win32, so it is not supported as a *production platform*.

### 2.2. Required Software

Required software for Linux and Windows include:

1. JavaTM 1.6.x, preferably from Sun, must be installed.
2. **ssh** must be installed and **sshd** must be running to use the Hadoop scripts that manage remote Hadoop daemons.

Additional requirements for Windows include:

1. [Cygwin](#) - Required for shell support in addition to the required software above.

### 2.3. Installing Software

If your cluster doesn't have the requisite software you will need to install it.

For example on Ubuntu Linux:

```
$ sudo apt-get install ssh
$ sudo apt-get install rsync
```

On Windows, if you did not install the required software when you installed cygwin, start the cygwin installer and select the packages:

- openssh - the *Net* category

## 3. Download

To get a Hadoop distribution, download a recent [stable release](#) from one of the Apache Download Mirrors.

## 4. Prepare to Start the Hadoop Cluster

Unpack the downloaded Hadoop distribution. In the distribution, edit the file `conf/hadoop-env.sh` to define at least `JAVA_HOME` to be the root of your Java installation.

Try the following command:

```
$ bin/hadoop
```

This will display the usage documentation for the **hadoop** script.

Now you are ready to start your Hadoop cluster in one of the three supported modes:

- Local (Standalone) Mode
- Pseudo-Distributed Mode
- Fully-Distributed Mode

## 5. Standalone Operation

By default, Hadoop is configured to run in a non-distributed mode, as a single Java process. This is useful for debugging.

The following example copies the unpacked `conf` directory to use as input and then finds and displays every match of the given regular expression. Output is written to the given output directory.

```
$ mkdir input
$ cp conf/*.xml input
$ bin/hadoop jar hadoop-*-examples.jar grep input output
'dfs[a-z. ]+'
$ cat output/*
```

## 6. Pseudo-Distributed Operation

Hadoop can also be run on a single-node in a pseudo-distributed mode where each Hadoop daemon runs in a separate Java process.

### 6.1. Configuration

Use the following `conf/hadoop-site.xml`:

```
<configuration>
```

<property>
<name>fs.default.name</name>
<value>hdfs://localhost:9000</value>
</property>
<property>
<name>mapred.job.tracker</name>
<value>localhost:9001</value>
</property>
<property>
<name>dfs.replication</name>
<value>1</value>
</property>
</configuration>

## 6.2. Setup passphraseless ssh

Now check that you can ssh to the localhost without a passphrase:

```
$ ssh localhost
```

If you cannot ssh to localhost without a passphrase, execute the following commands:

```
$ ssh-keygen -t dsa -P '' -f ~/.ssh/id_dsa
$ cat ~/.ssh/id_dsa.pub >> ~/.ssh/authorized_keys
```

## 6.3. Execution

Format a new distributed-filesystem:

```
$ bin/hadoop namenode -format
```

Start the hadoop daemons:

```
$ bin/start-all.sh
```

The hadoop daemon log output is written to the `$(HADOOP_LOG_DIR)` directory (defaults to `$(HADOOP_HOME)/logs`).

Browse the web interface for the NameNode and the JobTracker; by default they are

available at:

- NameNode - <http://localhost:50070/>
- JobTracker - <http://localhost:50030/>

Copy the input files into the distributed filesystem:

```
$ bin/hadoop fs -put conf input
```

Run some of the examples provided:

```
$ bin/hadoop jar hadoop-*-examples.jar grep input output  
'dfs[a-z. ]+'
```

Examine the output files:

Copy the output files from the distributed filesystem to the local filesystem and examine them:

```
$ bin/hadoop fs -get output output  
$ cat output/*
```

or

View the output files on the distributed filesystem:

```
$ bin/hadoop fs -cat output/*
```

When you're done, stop the daemons with:

```
$ bin/stop-all.sh
```

## 7. Fully-Distributed Operation

For information on setting up fully-distributed, non-trivial clusters see [Hadoop Cluster Setup](#).

*Java and JNI are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries.*