

# Creating a Resource Type, Part 3: Presentation

**Table of contents**

- 1 A Basic Presentation Pipeline.....2
- 2 Adding the CSS..... 3
- 3 Creating our First Person Document..... 3

## 1 A Basic Presentation Pipeline

Now the Lenya web application can create new person documents, but it won't be able to render them as HTML pages (or anything else) yet. In our resource type declaration we specified the format *xhtml*. According to this specification, we'll setup a basic presentation pipeline which converts our Foaf XML document to XHTML.

First we'll add the sitemap (`$MODULE_HOME/sitemap.xmap`). Note that some lines have been wrapped (marked with backslashes):

```
<?xml version="1.0" encoding="UTF-8"?>
<map:sitemap xmlns:map="http://apache.org/cocoon/sitemap/1.0">
  <map:pipelines>
    <map:pipeline>

      <!-- {format}.xml -->
      <map:match pattern="*.xml">
        <map:generate src="cocoon://{1}.xml/{page-envelope:publication-id}/ \
          {page-envelope:area}/{page-envelope:document-uuid}/ \
          {page-envelope:document-language}"/>
        <map:serialize type="xml"/>
      </map:match>

      <!-- {format}.xml/{pubId}/{area}/{uuid}/{language} -->
      <map:match pattern="*.xml/**/**/*">
        <map:generate src="lenya-document:{4}, lang={5}{link:rev}"/>
        <map:transform src="fallback://lenya/modules/person/xslt/foaf2xhtml.xsl"/>
        <map:serialize type="xml"/>
      </map:match>

      <!-- The icon for person nodes in the sitetree. -->
      <map:match pattern="icon/**/**/*">
        <map:read src="fallback://lenya/modules/person/resources/icons/person.gif"/>
      </map:match>

    </map:pipeline>
  </map:pipelines>
</map:sitemap>
```

The sitemap uses an XSLT stylesheet `$MODULE_HOME/xslt/foaf2xhtml.xsl` to render the XHTML view of the Foaf file:

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:foaf="http://xmlns.com/foaf/0.1/"
  xmlns="http://www.w3.org/1999/xhtml">

  <xsl:template match="rdf:RDF">
    <html>
      <body>
        <div id="body">
          <xsl:apply-templates select="foaf:Person"/>
        </div>
      </body>
    </html>
  </xsl:template>

  <xsl:template match="foaf:Person">
    <h2>Person Details</h2>
    <table class="person">
```

```

<tr>
  <th>Title:</th>
  <td><xsl:value-of select="foaf:title"/></td>
</tr>
<tr>
  <th>Given name:</th>
  <td><xsl:value-of select="foaf:givenname"/></td>
</tr>
<tr>
  <th>Family name:</th>
  <td><xsl:value-of select="foaf:family_name"/></td>
</tr>
<tr>
  <th>E-Mail:</th>
  <td>
    <xsl:variable name="mbox" select="foaf:mbox/@rdf:resource"/>
    <a href="{ $mbox }">
      <xsl:value-of select="substring-after($mbox, 'mailto:')"/>
    </a>
  </td>
</tr>
<tr>
  <th>Phone:</th>
  <td>
    <xsl:variable name="phone" select="foaf:phone/@rdf:resource"/>
    <xsl:value-of select="substring-after($phone, 'tel:')"/>
  </td>
</tr>
<tr>
  <th>Homepage:</th>
  <td>
    <xsl:variable name="homepage" select="foaf:workplaceHomepage/@rdf:resource"/>
    <a href="{ $homepage }"><xsl:value-of select="$homepage"/></a>
  </td>
</tr>
</table>
</xsl:template>

</xsl:stylesheet>

```

## 2 Adding the CSS

The default publication allows to add custom CSS files for each resource type. We want to style our table headers a bit, so we add the file `pubs/default/resources/shared/css/person.css` with the following content:

```

table.person { font-size: small; }
table.person th {
  font-weight: normal;
  color: #999999;
  text-align: left;
  padding-right: 1em;
}

```

## 3 Creating our First Person Document

Now it's time to check out if everything works as expected. First, we build the Lenya web application to deploy our new resource type. If Lenya is running, shut it down. Go to `$LENYA_HOME` and execute

```
./build.sh
```

When the build has finished, start the Jetty server:

```
./lenya.sh
```

Now go to <http://localhost:8888/default/authoring/index.html> and log in as user "lenya". The *File* menu should now contain an item *New Person Document*. But before creating person documents, we'll add a new top level XHTML document *People*:

- File -> New XHTML Document
- Node Name: people
- Navigation Title: People

You end up on the *People* page. Now you can create a new person document as a child of this document by selecting the *New Person Document* menu item:

### New Document

Parent Path: /people

Node Name\*:   
(No whitespace, no special characters)

Navigation Title\*:

Visible in Navigation\*:  ▼

Relation\*:  child  sibling after

Language\*:  ▼

Creator:

Subject:

Publisher:

Date: 2007-05-25 17:06:15

Rights:

Page Layout:  Default Sample

\* required fields

After hitting OK, you're redirected to the newly created person document:

Home Tutorial Concepts Apache Lenya Links Features Resource Type Examples News

» People » Homer Simpson  Go

### Person Details

Title: Mr  
Given name: Homer  
Family name: Simpson  
E-Mail: [chunkylover53@aol.com](mailto:chunkylover53@aol.com)  
Phone: 555-555-555  
Homepage: <http://powerplantspringfield.com>

*This page has not been published yet.*

UK Germany India Spain France

In the [next section](#) ( ../.../docs/2\_0\_x/tutorials/resourcetype/part4.html) we'll make our person documents editable.