

# ZooKeeper Quota's Guide

## A Guide to Deployment and Administration

by

### Table of contents

1 Quotas.....	2
1.1 Setting Quotas.....	2
1.2 Listing Quotas.....	2
1.3 Deleting Quotas.....	2

## 1. Quotas

ZooKeeper has both namespace and bytes quotas. You can use the ZooKeeperMain class to setup quotas. ZooKeeper prints *WARN* messages if users exceed the quota assigned to them. The messages are printed in the log of the ZooKeeper.

```
$java -cp
zookeeper.jar:src/java/lib/log4j-1.2.15.jar/conf:src/java/lib/jline-0.9.9
\ org.apache.zookeeper.ZooKeeperMain -server host:port
```

The above command gives you a command line option of using quotas.

### 1.1. Setting Quotas

You can use *setquota* to set a quota on a ZooKeeper node. It has an option of setting quota with *-n* (for namespace) and *-b* (for bytes).

The ZooKeeper quota are stored in ZooKeeper itself in */zookeeper/quota*. To disable other people from changing the quota's set the ACL for */zookeeper/quota* such that only admins are able to read and write to it.

### 1.2. Listing Quotas

You can use *listquota* to list a quota on a ZooKeeper node.

### 1.3. Deleting Quotas

You can use *delquota* to delete quota on a ZooKeeper node.